SAFETY DATA SHEET



1. Identification

Product identifier UNI-REZ™ 2228

Other means of identification

SDS number 9179

Product Code 200000000811

Recommended use Industrial uses: Uses of substances as such or in preparations at industrial sites. Formulation

[mixing] of preparations and/or re-packaging (excluding alloys).

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Company Kraton Chemical, LLC
Address P.O. Box 550850
Jacksonville, FL

Zip 32255-0850

Country USA

 Phone Number
 904-928-8700

 Alternate Phone Number
 800-526-5294

 Fax Number
 904-928-8780

Emergency-US CHEMTREC 800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Combustible dust

Label elements

Hazard symbol None.

Signal word Warning

Hazard statement May form combustible dust concentrations in air.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Prevent dust accumulation to minimize

explosion hazard. Observe good industrial hygiene practices.

Response Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Polyamide Resin		Proprietary	99-100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Material name: UNI-REZ™ 2228

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Dusts may irritate the respiratory tract, skin and eyes.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special Treat symptomatically.

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing media carefully to avoid creating airborne dust.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

High concentration of airborne dust may form explosive mixture with air. Static charges generated by emptying package in or near flammable vapor may cause flash fire. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Wear suitable protective equipment. Move

containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

Conditions for safe storage, including any incompatibilities Keep containers tightly closed in a dry, cool and well-ventilated place. Store at ambient temperature and atmospheric pressure. Store away from incompatible materials (see Section 10 of the SDS).

Material name: UNI-REZ™ 2228 SDS US

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

Additional components	Туре	Value	Form
Dust	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove Hand protection

supplier.

Wear suitable protective clothing. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eye wash fountain and emergency showers are recommended.

9. Physical and chemical properties

Solid. **Appearance** Physical state Solid. **Form** Granular. Amber Color

Mild. Amine-like. Odor Odor threshold Not available. Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point

> 200.8 °F (> 93.8 °C) Cleveland Open Cup

0 n-BuAc=1 estimated **Evaporation rate**

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Vapor pressure < 0.001 mm Hg at 20°C

Vapor density Not available.

Relative density 0.97 at 25°C/25°C (water=1)

Solubility(ies)

< 0.1 % at 25°C Solubility (water) Partition coefficient Not available. (n-octanol/water)

Material name: UNI-REZ™ 2228 9179 Version #: 4.0 Revision date: 07-29-2022 Issue date: 12-29-2014

SDS US

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 1800 cP Brookfield at 160°C

Other information

Chemical family Polyamide Resin **Density** 970.00 kg/m³

Percent volatile 0 % by weight estimated

Softening point 230 °F (110 °C) Ring & Ball

Weighted solids 100 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Strong oxidizing agents. Keep away from heat, sparks and open flame. Contact with incompatible

materials. Minimize dust generation and accumulation.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide,

water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicityBased on available data, the classification criteria are not met.

Components	Species	lest Results
Polvamide Resin		

Acute

Oral

LD50 Rat > 5000 mg/kg, 14 days At this dose no

death occurred.;Data is for similar product.;

OECD 401

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Skin sensitization

Polyamide Resin Buehler Test, Not a skin sensitizer.; Data is for similar

product.; Result: Negative Species: Guinea pig Organ: Skin

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Material name: UNI-REZ™ 2228

^{*} Estimates for product may be based on additional component data not shown.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not available.

Specific target organ toxicity -

repeated exposure

Not available.

Aspiration hazard

Not available.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Polyamide Resin			
Acute			
	EC50	Bacteria (Pseudomonas putida)	> 1000 mg/l, 16 hr >> Water solubility; Data is for similar product.;
Aquatic			
Crustacea	NOEC	Water flea (Daphnia magna)	> 1000 mg/l, 48 hr Data is for similar product.; OECD 202;
Acute			
Crustacea	EL50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hr >> Water solubility; Data is for similar product.; OECD 202;

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

Material name: UNI-REZ™ 2228

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components are either listed on the US EPA TSCA Inventory list and

designated as "active" or are exempt from listing.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard

Combustible dust

categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

16. Other information, including date of preparation or last revision

12-29-2014 Issue date **Revision date** 07-29-2022

Version # 4.0

Further information Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the

Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Health: 1 NFPA ratings

Flammability: 1 Instability: 0

NFPA ratings



Material name: UNI-REZ™ 2228 SDS US 6/7

Disclaimer

KRATON CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information set forth in this document, as of the date of this document, is based on present knowledge, obtained from reliable sources and made to our reasonable ability and in good faith. Such information is made without any warranty or guarantee whatsoever, and shall establish no legal duty or responsibility on the part of the author(s), their employer or its affiliates. The information given is designed only as guidance and its completeness is not guaranteed. The information is not a guarantee of any specific product properties, features, qualities or specifications.

The information relates only to the specific product designated as shipped, and may not be valid for such product used in combination with any other materials or products, or in any process, unless expressly specified in this document. Nothing set forth in this document shall be construed as a recommendation or license to use any product in conflict with, or as claimed by, any existing patents rights. The user alone must finally determine whether a contemplated use of a product will infringe any such patents. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities are in compliance with all Local, Federal and International Legislation and Local Permits.

We, for ourselves and on behalf of our affiliates, expressly disclaim any and all liability for any damages or injuries arising out of any activities relating in any way to the information set forth in this document. Due to the proliferation of sources for information, we are not and cannot be responsible for SDSs obtained from any other source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

*KRATON, the KRATON logo, the "Green Super Drop" logo, 1101, ABIETA, AQUATAC, BiaXam, BI-THIN, CENTURY, CENWAX, CirKular+, ELEXAR, ELLAMERA, E-LEXAR, HiMA, IMSS, IPD, NEXAR, PER-SUST, PriMul, RAD-THICK, REFLECTAID, REvolution, SYLFAT, SYLVABIND, SYLVABLEND, SYLVACLEAR, SYLVACOTE, SYLVADERM, SYLVAFUEL, SYLVAGEL, SYLVAGUM, SYLVALITE, SYLVAMIN, SYLVAPINE, SYLVAPRINT, SYLVARES, SYLVAROAD, SYLVAROS, SYLVASOLV, SYLVATAC, SYLVATAL, SYLVATRAXX, TER-SET, UNICLEAR, UNIDYME, UNIFLEX, UNI-REZ, UNI-TAC, and ZONATAC are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2022 Kraton Corporation

Revision information

Physical & Chemical Properties: Multiple Properties

Regulatory information: Toxic Substances Control Act (TSCA)

Other information, including date of preparation or last revision: Disclaimer

GHS: Acute Toxicity Estimate

9179 Version #: 4.0 Revision date: 07-29-2022 Issue date: 12-29-2014