KRATON

K0717 Mailiao 5/13/2022

KRATON™ MD1542 V

Data Document

Identifier: K717DDa22A

Description

Kraton MD1542 V is a clear, block copolymer based on styrene and ethylene/butylene with a total polystyrene content of 28.6~%. It is supplied from Taiwan in the physical form outlined below.

• Kraton MD1542 VO - supplied as dusted, dense pellet

The product exhibits the following characteristics:

- · high strength
- medium melt flow designed for good processability for extrusion and injection molding process

Note: This Kraton polymer product is a development product. Thus, its properties and chemical composition may change based on market feedback. Kraton Polymers reserves the right to change specifications and/or discontinue production of the product.

Sales Specifications							
<u>Property</u>	Test Method	<u>Units</u>	Sales Specification Range	<u>Notes</u>			
Melt Flow, 230C/2160g	ASTM D1238	g/10 min	12.0 TO 20.0				
Antioxidant	KM 08	%m	0.06 TO 0.14	a			
Volatile Matter	KM 04	%m	<= 1.0				
Total Extractables	KM 05	%m	<= 1.0				
a Non-staining phenolic antioxidant							

Typical Properties (These are typical values and may not routinely be measured on finished product)							
<u>Property</u>	Test Method	<u>Units</u>	<u>Typical Value</u>	Notes			
Hardness, Shore A (10 sec)	ASTM D 2240	Shore A (10 sec)	44				
Melt Index 230C, 2.16 kg	ASTM D 1238	gms/10 min.	15.5				

Packaging

Kraton Polymers are available in a number of different package types. For information specific to this grade, please contact your local Kraton Polymers representative.

KRATON and the Kraton logo are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2022 Kraton Corporation

End Use Requirements

If the finished article is intended for use in food contact and packaging applications, toys, or human contact areas, manufacturers of the final product should observe all relevant regulations. Some of these regulations require tests to be carried out on the final product, e.g. migration. These are the responsibility of the final product manufacturer.

Information on the food packaging clearances of individual products is available from Kraton Polymers.

Safety and Handling Precautions

Read the GHS Data Sheet carefully and thoroughly before beginning any work.

Legal Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

For Further Information

U.S.A Headquarters

Kraton Polymers U.S. LLC 15710 John F. Kennedy Blvd. Suite 300 Houston, Texas 77032 +1-800-4-KRATON (800-457-2866) info@kraton.com

Asia Pacific

Regional Headquarter/ Innovation Center Rm 2201, No.588, West Nan Jing Road 100 Century Avenue Shanghai, 200041, PR China +86 21 2082 3888 info.cn@kraton.com

Europe, Middle East, Africa

Kraton Polymers Nederland B.V. Transistorstraat 16 NL - 1322 CE Almere The Netherlands +31 36 546 2846 info@kraton.com