

SYLFAT™ 2LT Tall Oil Fatty Acid

PRODUCT DATA SHEET

SYLFAT 2LT Tall Oil Fatty Acid (TOFA) is refined from selected crude tall oil grades aimed to achieve a low temperature performance, under carefully controlled process conditions and extended analysis for consistent quality. The utility of SYLFAT 2LT can be found in the long carbon chain (C18), acid function of the carboxyl group (COOH), unsaturation of the double bonds and consistently low cloud point and pour point. SYLFAT 2LT is developed for applications requiring low temperature properties.

FEATURES:

- Low content of rosin acids and unsaponifiables
- Clarity at low temperatures
- SYLFAT 2LT tall oil fatty acid contains 100% USDA certified biobased content

POTENTIAL APPLICATIONS:

 Component for lubricity improvers

SALES SPECIFICATIONS

Property	Test Method*	Specification
Acid Number (mg KOH/g)	AQCM 001	194 – 199
Colour, Gardner, Photometer	AQCM 002	3.0 - 4.5
Free Rosin Acids (%)	AQCM 010	1.0 - 2.0
Unsaponifiables (%)	AQCM 011	Max 2.0
Cloud Point (°C)	AQCM 061	Max -4
Viscosity at 20 °C (cSt)	AQCM 234	20 - 50
Density at 15 °C (g/cm³)	AQCM 234	0.89 - 0.93
*Kraton test methods are available upon request		

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898

www.kraton.com



SOLUBILITY	SYLFAT™ 2LT Tall Oil Fatty Acid is <u>soluble</u> in alcohols, aromatics, esters and ketones, and <u>insoluble</u> in water.
COMPATIBILITY	SYLFAT 2LT is compatible with other liquid fatty acids and vegetable oils.
PACKAGING	SYLFAT 2LT is delivered as a liquid in tank trucks, ISO containers, rail cars, flexi tanks, IBC's or steel drums (as available). Typical delivery temperature is 10 – 30 °C (50 – 86 °F).
STORAGE RECOMMENDATION	SYLFAT 2LT should be stored dry, below 25 °C (77 °F) and away from direct sunlight. If precipitation occurs when stored at temperatures below the product's cloud point, it does not affect the use of the product as a chemical raw material. Slight heating to about 40 °C (104 °F) dissolves the precipitated material. Since colour changes of >1 Gardner unit can be seen over time due to oxygen or heat exposure, testing of product in applications sensitive to colour is recommended prior to use.



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, SHELF-LIFE OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS. The user assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo and SYLFAT are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2021 Kraton Corporation

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439

Shanghai (CN): + 86 21 6434 8898 www.kraton.com