

SYLFAT™ FA1 Tall Oil Fatty Acid

PRODUCT DATA SHEET

SYLFAT FA1 Tall Oil Fatty Acid (TOFA) combines a long carbon chain (C18) of relatively high unsaturation with the acid functionality of a carboxyl group (-COOH).

FEATURES:

- Low viscosity, liquid long fatty acid chain
- C18 monocarboxylic acid functionality
- Low saturated fatty acid content
- Reactive polyunsaturation
- SYLFAT FA1 tall oil fatty acid contains 100% USDA certified biobased content

POTENTIAL APPLICATIONS:

- Alkyd Resins
- Dimer Acids
- Oilfield chemicals
- Asphalt emulsifiers
- Lubricant additives
- Metalworking fluids
- Plasticizers
- Textile drawing lubricants
- Specialty industrial and household cleaners

SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Acid Number(mgKOH/g)	AQCM 001	193 - 205	194
Color, Gardner	AQCM 002	5 Maximum	4.5
Rosin Acids, %	AQCM 010	3 Maximum	2.5

*Kraton test methods are available upon request

TYPICAL PROPERTIES

Property	Test Method*	Typical Value
Unsaponifiabiles	AQCM 011	2.2
Iodine Number	AQCM 009	125

*Kraton test methods are available upon request

SOLUBILITY	SYLFAT™ FA1 tall oil fatty acid is <u>soluble</u> in alcohols, aromatics, esters and ketones and <u>insoluble</u> in water.
COMPATIBILITY	SYLFAT FA1 tall oil fatty acid is compatible with other liquid fatty acid and vegetable oils.
PACKAGING	SYLFAT FA1 tall oil fatty acid is delivered as liquid in 420 lb net steel drums or as bulk in totes, tank trucks, or tank cars (as available).
STORAGE RECOMMENDATION	<p>SYLFAT FA1 Tall Oil Fatty Acid should be stored dry and below 77 °F, (25 °C) and away from direct sunlight. The product must be retested after longer storage to ensure the properties are within specification limits. Since colour changes of >1 Gardner unit can be seen over time due to oxygen or heat exposure, testing of product in applications sensitive to color is recommended prior to use.</p> <p>If precipitation occurs, it does not affect the use of the product as a chemical raw material. Slight heating to about 104 °F, (40 °C) dissolves the precipitated material.</p>



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, SHELF-LIFE OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS. The user assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo and SYLFAT are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2021 Kraton Corporation

Contact us:
 Almere (NL): +31 (0)36 54 62 800
 Savannah (US): + 1 (912) 238-6439
 Shanghai (CN): + 86 21 6434 8898
www.kraton.com