# KRATON

### SYLVABLEND<sup>™</sup> PF 60 Tall Oil Pitch

PRODUCT DATA SHEET

SYLVABLEND PF 60 tall oil pitch is a bioliquid made from tall oil pitch and other distillates. It is used as a low-sulfur replacement of heavy fuel oils in mainly power plants.

SYLVABLEND PF 60 tall oil pitch contains 100% USDA certified biobased content.

Test Method*	Specification	Typical Value
AQCM 001 ASTM D465	Max 130	90
AQCM 008 ASTM D890	Max 0.5	<0.2
AQCM 004 ASTM D2196	Max 600	100 - 300
AQCM 193 ASTM D5453	Max 0.40	<0.2
AQCM 007 ASTM D93 or D3278	Min 100	>150
AQCM 015 ASTM D803	Max 0.6	<0.3
	AQCM 001 ASTM D465 AQCM 008 ASTM D890 AQCM 004 ASTM D2196 AQCM 193 ASTM D5453 AQCM 007 ASTM D93 or D3278 AQCM 015	AQCM 001 ASTM D465 Max 130   AQCM 008 ASTM D890 Max 0.5   AQCM 004 ASTM D2196 Max 600   AQCM 193 ASTM D5453 Max 0.40   AQCM 007 ASTM D93 or D3278 Min 100   AQCM 015 Max 0.6

### SALES SPECIFICATIONS

 $\ast {\sf KRATON}\,$  test methods are available upon request

### TYPICAL PROPERTIES

Property	Test Method*	Typical Value
Heat of Combustion (MJ/kg)	ASTM D240	37.6
Pour Point (°C)	ASTM D97	<20
Density at 50 °C (kg/m <sup>3</sup> )	ASTM D4052	950
*KRATON test methods are available upon request		

## KRATON

#### PACKAGING

SYLVABLEND<sup>m</sup> PF 60 Tall Oil Pitch is delivered as a liquid in heated tank trucks or as boat shipment.



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

#### Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo, and SYLVABLEND are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2022 Kraton Corporation

Contact us: Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898 www.kraton.com