

SYLVARES™ 1150 Terpene Phenol

PRELIMINARY PRODUCT DATA

Subject to change

SYLVARES 1150 tackifier is a thermoplastic terpene phenolic resin designed for tackifying hot melt adhesives to provide superior adhesion and thermal-stability properties. This high heat resistance resin exhibits excellent compatibility and tackifying properties for use in styrenic-block-co-polymers and for solvent acrylic based pressure sensitive adhesives. This resin can also be used to tackify metallocene polymers.

FEATURES

- · High softening point
- Broad compatibility
- Thermally stable
- SYLVARES 1150 tackifier contains 83% USDA certified biobased content

POTENTIAL APPLICATIONS

- PSA Tapes
- PSA Labels
- Packaging

SALES SPECIFICATIONS

Property	Test Method*	Specification
Softening Point (°C)	AQCM 003, (Mettler)	145-155
Color, neat (Gardner)	AQCM 002	Max. 6
*Kraton test methods are available upon request		

Contact us: Almere (NL): +31 (0)36 54 62 800

Savannah (US): + 1 (912) 238-6439 Shanghai (CN): + 86 21 6434 8898

www.kraton.com

KRATON

SOLUBILITY	SYLVARES™ 1150 terpene phenolic tackifier is <u>soluble</u> in:	
	aromatic / aliphatic solvents like hexane & tolueneesters and ketones like ethylacetate and acetone	
	- longer chain alcohols like propanol, pentanol, butanol	
	SYLVARES 1150 terpene phenolic tackifier is insoluble in:	
	- smaller alcohols like ethanol	
COMPATIBILITY	SYLVARES 1150 tackifier is compatible with:	
	- many polyolefins	
	- styrenic block copolymers	
	- EVA	
	- some acrylics	
PACKAGING	SYLVARES 1150 terpene phenolic tackifier is delivered as	
	flakes in 50lb. paper bags.	
STORAGE RECOMMENDATION	To prevent remassing, keep away from direct sun light or	
	other sources of heat. Product stored or transported at	
	higher temperatures should be evaluated for impact on	
	performance before use.	



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo, and SYLVARES are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2019-2021 Kraton Corporation

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898

www.kraton.com