

SYLVARES™ TP 96 Terpene Phenol

PRODUCT DATA SHEET

SYLVARES TP 96 resin is a low softening point terpene phenolic resin having broad polymer compatibility. This thermoplastic resin is designed to tackify hot melt and pressure sensitive adhesives providing improved tack, peel and flexibility for EVA, SIS and acrylic based systems. When formulated as a co-resin, this product will significantly improve performance and properties of styrenic block copolymers based adhesives with limited impact on heat resistance.

FEATURES

- Broad polymer compatibility
- Can be used as co-tackifier SBC systems
- Improved adhesion to difficult substrates
- SYLVARES TP 96 resin contains 83% USDA certified biobased content

POTENTIAL APPLICATIONS

- PSA Tapes
- Packaging
- Assembly

SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Softening Point (°C)	AQCM 003	92 – 98	96
Color, Gardner neat	AQCM 002	Max. 8	6


*Kraton test methods are available upon request

TYPICAL VALUES

Property	Test Method*	Typical Value
Glass Transition Temperature (°C)	AQCM 218	50
Viscosity, Brookfield @ 125°C (cps.)	AQCM 004	8850
Viscosity, Brookfield @ 150°C (cps.)		455
Viscosity, Brookfield @ 177°C (cps.)		75

*Kraton test methods are available upon request

<p>SOLUBILITY</p>	<p>SYLVARES™ TP 96 tackifier is <u>soluble</u> in:</p> <ul style="list-style-type: none"> - aromatic / aliphatic solvents like hexane & toluene - esters and ketones like ethylacetate and acetone - longer chain alcohols like propanol, pentanol, butanol <p>SYLVARES TP 96 tackifier is <u>insoluble</u> in:</p> <ul style="list-style-type: none"> - smaller alcohols like ethanol
<p>COMPATIBILITY</p>	<p>SYLVARES TP 96 tackifier is compatible with:</p> <ul style="list-style-type: none"> - many polyolefins - styrenic block copolymers - EVA - some acrylics
<p>PACKAGING</p>	<p>SYLVARES TP 96 tackifier is delivered as flakes in 50 lb. paper bags.</p>
<p>STORAGE RECOMMENDATION</p>	<p>Storage and transit dry and below 25°C / 77°F is recommended. To prevent remassing, keep away from direct sun light or other sources of heat. Product stored or transported at higher temperatures should be evaluated for impact on performance before use.</p>



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

KRATON, the KRATON logo, and SYLVARES are trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2019-2021 Kraton Corporation

Contact us:
 Almere (NL): +31 (0)36 54 62 800
 Savannah (US): + 1 (912) 238-6439
 Shanghai (CN): + 86 21 6434 8898
www.kraton.com