SYLVARES™ TR M1115 Polyterpene

PRODUCT DATA
SHEET

SYLVARES TR M1115 polyterpene resin is a biorenewable tackifier made from selected terpene monomers. This product can be used to tackify natural rubber, synthetic elastomer, and some polyolefin adhesives. The aliphatic nature of this product allows compatibility with the mid-block of styrene-isoprene-styrene block copolymers while limiting interaction with the styrenic end-blocks providing a balance of tack, peel, cohesive strength, and heat resistance. It has a narrower molecular weight distribution, which improves compatibility with some adhesive elastomers.

FEATURES

POTENTIAL APPLICATIONS

- Aliphatic compatibility
- · Thermally stable
- · Light color
- SYLVARES TR M1115 polyterpene contains 100% USDA certified biobased content
- PSA Tapes
- PSA Labels
- Non-wovens

SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Softening Point (°C)	AQCM 003	112 - 118	115
Color, neat (Gardner)	AQCM 002	Max. 3	2

^{*}Kraton test methods are available upon request

*Kraton test methods are available upon request

TYPICAL VALUES

Property	Test Method*	Typical Value
Glass Transition Temperature (°C)	AQCM 218	60
Viscosity, Brookfield (150°C), cps.		10130
Viscosity, Brookfield (177°C), cps.	AQCM 004	908
Viscosity, Brookfield (190°C), cps.		390

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898 www.kraton.com

KRATON

	SYLVARES™ TR M1115 polyterpene resin is <u>soluble</u> in:	
SOLUBILITY	 aromatic / aliphatic solvents like hexane & toluene 	
	SYLVARES TR M1115 polyterpene resin is insoluble in:	
	- alcohols like ethanol, propanol, butanol	
	 esters and ketones like ethylacetate and acetone 	
COMPATIBILITY	SYLVARES TR M1115 tackifier is compatible with:	
	- many polyolefins	
	- SIS block copolymers	
PACKAGING	SYLVARES TR M1115 tackifier is delivered as pastilles in 50 lb. paper bags or 1000 kg big bags.	
STORAGE RECOMMENDATION	To preserve product quality, storage and transit dry and below 30°C / 86°F is recommended. To prevent remassing, keep away from direct sun light or other sources of heat. Product stored or transported at higher temperatures should be evaluated for impact on performance before use.	



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, SHELF-LIFE OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS. The user assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

*KRATON, the Kraton logo, and SYLVARES are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2019-2022 Kraton Corporation

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898

www.kraton.com