

SYLVATAL™ 20S Distilled Tall Oil

PRODUCT DATA SHEET

SYLVATAL 20S Distilled Tall Oil (DTO), with a 20% rosin acid content, combines the advantages of fatty acids and rosin acids.

FEATURES:

- Fluid at room temperature
- Low saturated fatty acid content
- Monocarboxylic acid functionality
- SYLVATAL 20S distilled tall oil contains 100% USDA certified biobased content

POTENTIAL APPLICATIONS:

- Metal working fluids
- Oilfield chemicals
- Soaps and cleaners
- Alkyd resins
- Varnishes

SALES SPECIFICATIONS

Property	Test Method*	Specification	Typical Value
Acid Number (mg KOH/g)	AQCM 001	Min 186	192
Colour, Gardner, Photometer	AQCM 002	Max 7.0	4.9
Free Rosin Acids (%)	AQCM 010	18 - 22	20
Unsaponifiables (%)	AQCM 011	Max 3.5	1.6
*Kraton test methods are available upon request			

Contact us: (0)36 54 62 800

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898

www.kraton.com

KRATON

SOLUBILITY	SYLVATAL™ 20S Distilled Tall Oil is <u>soluble</u> in alcohols, aromatics, esters and ketones, and <u>insoluble</u> in water.	
COMPATIBILITY	SYLVATAL 20S Distilled Tall Oil is compatible with other liquid fatty acids and vegetable oils.	
PACKAGING	SYLVATAL 20S Distilled Tall Oil is delivered as a liquid in tank trucks or ISO containers. Typical bulk delivery temperature is $25-40^{\circ}\text{C}$ (77 – 104 °F).	
STORAGE RECOMMENDATION	SYLVATAL 20S Distilled Tall Oil should be stored dry and below 25 °C (77 °F), and away from direct sunlight. This product has a tendency to crystallize after holding for extended periods of time at ambient temperatures of 25 °C (77 °F) or lower. If precipitation occurs, it does not affect the use of the product as a chemical raw material. Slight heating to about 40 °C (104 °F) dissolves the precipitated material.	



The USDA Certified Biobased Product label is a certification mark of the U.S. Department of Agriculture.

Disclaimer

We cannot anticipate all circumstances, conditions or applications in which this information, our products, or the products of other suppliers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or for the safety or suitability of our products, either alone or in combination with other products. The user of our products bears the responsibility of determining their suitability for a particular application or formulation, or determining that the products or their use do not infringe any intellectual property. Unless otherwise stated in writing, WE MAKE NO WARRANTY REGARDING THE INFORMATION PROVIDED HEREIN OR OUR PRODUCT, EITHER EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, SHELF-LIFE OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS. The user assumes all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

*KRATON, the Kraton logo, and SYLVATAL are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2021 Kraton Corporation

Contact us:

Almere (NL): +31 (0)36 54 62 800 Savannah (US): +1 (912) 238-6439 Shanghai (CN): +86 21 6434 8898

www.kraton.com