

1. Identification

Product identifier	SYLVAROS™ DR 731D
Other means of identification	
SDS number	8820
Product Code	200000000367
Recommended use	Industrial uses: Uses of substances as such or in preparations at industrial sites. Formulation [mixing] of preparations and/or re-packaging (excluding alloys).
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company	Kraton Chemical, LLC
Address	P.O. Box 550850 Jacksonville, FL
Zip	32255-0850
Country	USA
Phone Number	904-928-8700
Alternate Phone Number	800-526-5294
Fax Number	904-928-8780
Emergency-US	CHEMTREC 800-424-9300

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Combustible dust
Label elements	
Hazard symbol	None.
Signal word	Warning
Hazard statement	May form combustible dust concentrations in air.
Precautionary statement	
Prevention	Prevent dust accumulation to minimize explosion hazard. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Observe good industrial hygiene practices.
Response	Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	May form combustible dust concentrations in air.
Supplemental information	None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Rosin		8050-09-7	100

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). Apply extinguishing media carefully to avoid creating airborne dust.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	High concentration of airborne dust may form explosive mixture with air. Static charges generated by emptying package in or near flammable vapor may cause flash fire. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Wear suitable protective equipment. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). The product is immiscible with water and will sediment in water systems. Stop the flow of material, if this is without risk. Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water. Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills to original containers for re-use.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Follow all SDS/label precautions even after container is emptied because they may retain product residues. May ignite (with a sufficient source of heat) if spread as a thin film or absorbed onto porous or fibrous material. Porous material such as rags, paper, insulation, or organic clay may spontaneously combust when wetted with this material and heated.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store at ambient temperature and atmospheric pressure.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

Additional components	Type	Value	Form
Dust	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Rosin (CAS 8050-09-7)	TWA	0.001 mg/m ³	Inhalable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. When handling hot material, use heat resistant gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Wear suitable gloves tested to EN374. Recommended gloves include rubber, neoprene, nitrile or viton. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness should be typically greater than 0.35 mm. This recommendation is advisory only. It may not be appropriate for all workplaces. It should not be construed as offering an approval for any specific use scenario. A hazard assessment should be conducted prior to use to ensure suitability of gloves for specific work environments and processes.

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eye wash fountain and emergency showers are recommended.

9. Physical and chemical properties

Appearance

Solid.

Physical state

Solid.

Form

Solid.

Color

Amber.

Odor

Rosin

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

> 185 - < 203 °F (> 85 - < 95 °C) Ring & Ball

Initial boiling point and boiling range

>392 °F (>200 °C)

Flash point

393.8 °F (201.0 °C) estimated
386.6 °F (197.0 °C) Cleveland Open Cup

Evaporation rate	0 (n-BuAc=1) estimated
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	4 hPa estimated <0.001 mm Hg at 20°C
Vapor density	Not available.
Relative density	1.06 at 25°C/25°C (water=1)
Solubility(ies)	
Solubility (water)	<0.1 % at 20°C
Partition coefficient (n-octanol/water)	3.6
Auto-ignition temperature	572 °F (300 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Chemical family	Rosin
Density	1060.00 kg/m3 at 20°C
Percent volatile	0 % by weight. estimated
Weighted solids	100 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Strong oxidizing agents. Keep away from heat, sparks and open flame. Contact with incompatible materials. Minimize dust generation and accumulation.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Rosin	Irritation Corrosion - Eye, No eye irritation; OECD 405 Result: negative Species: New Zealand white rabbit Organ: Eye Test Duration: 72 hr
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Rosin (CAS 8050-09-7)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours

Components	Species	Test Results
	Sprague-Dawley rat	> 2000 mg/kg, 24 hr At this dose no death occurred.; OECD 402
Oral LD50	Rat	> 2000 mg/kg 2800 mg/kg OECD 402
	Sprague-Dawley rat	5000 - 10000 mg/kg, 14 d Data is for similar product.;
NOEL	Sprague-Dawley rat	1000 ppm, 2 wk

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Corrosivity Rosin		Irritation Corrosion - Skin, Non-irritating to the skin.; OECD 404 Result: negative Species: New Zealand white rabbit Test Duration: 72 hr
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Eye Contact Rosin		Irritation Corrosion - Eye, No eye irritation; OECD 405 Result: negative Species: New Zealand white rabbit Organ: Eye Test Duration: 72 hr
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Skin sensitization Rosin		Buehler Test, Not a skin sensitizer.; OECD 406 Result: Negative Species: Guinea pig Organ: Skin Local Lymph Node Assay - Lowest Concentration Producing Reaction, Not a skin sensitizer.; OECD 429 Result: Negative Species: Mouse Organ: Skin
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Mutagenicity Rosin		Ames test, Not mutagenic.; OECD 471; Result: Negative Species: Salmonella typhimurium Chromosome aberration test in vitro, Not mutagenic.; OECD 473; Result: Negative Species: Human In vitro gene mutation study in mammalian cells, Not mutagenic.; OECD 476; Result: Negative Species: Mammal
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity	Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens	Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Rosin (CAS 8050-09-7)	EC50	Activated sewage sludge	> 10000 mg/l, 3 hr OECD 209;
Aquatic			
Algae	EL50	Green algae (Selenastrum capricornutum)	> 1000 mg/l, 72 hr OECD 201;
Crustacea	EL50	Water flea (Daphnia magna)	911 mg/l, 48 hr OECD 202;

* Estimates for product may be based on additional component data not shown.

Persistence and degradability The product is biodegradable.

Biodegradability

Percent degradation (Aerobic biodegradation)

Rosin 64 % OECD 301B
Result: Readily biodegradable.
Species: Activated sewage sludge
Test Duration: 28 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

SYLVAROS™ DR 731D 3.6

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components are either listed on the US EPA TSCA Inventory list and designated as "active" or are exempt from listing.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Combustible dust

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

16. Other information, including date of preparation or last revision

Issue date 02-05-2015

Revision date 06-14-2023

Version # 7.0

Further information Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

NFPA ratings Health: 1
Flammability: 1
Instability: 0

NFPA ratings



Disclaimer

KRATON CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information set forth in this document, as of the date of this document, is based on present knowledge, obtained from reliable sources and made to our reasonable ability and in good faith. Such information is made without any warranty or guarantee whatsoever, and shall establish no legal duty or responsibility on the part of the author(s), their employer or its affiliates. The information given is designed only as guidance and its completeness is not guaranteed. The information is not a guarantee of any specific product properties, features, qualities or specifications.

The information relates only to the specific product designated as shipped, and may not be valid for such product used in combination with any other materials or products, or in any process, unless expressly specified in this document. Nothing set forth in this document shall be construed as a recommendation or license to use any product in conflict with, or as claimed by, any existing patents rights. The user alone must finally determine whether a contemplated use of a product will infringe any such patents. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities are in compliance with all Local, Federal and International Legislation and Local Permits.

We, for ourselves and on behalf of our affiliates, expressly disclaim any and all liability for any damages or injuries arising out of any activities relating in any way to the information set forth in this document. Due to the proliferation of sources for information, we are not and cannot be responsible for SDSs obtained from any other source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

*KRATON, the KRATON logo, the "Green Super Drop" logo, 1101, ABIETA, AQUATAC, BiaXam, BI-THIN, CENTURY, CENWAX, CirKular+, ELEXAR, ELLAMERA, E-LEXAR, HIMA, IMSS, IPD, NEXAR, PER-SUST, PriMul, RAD-THICK, REFLECTAID, REvolution, SYLFAT, SYLVABIND, SYLVABLEND, SYLVACLEAR, SYLVACOTE, SYLVADERM, SYLVAFUEL, SYLVAGEL, SYLVAGUM, SYLVALITE, SYLVAMIN, SYLVAPINE, SYLVAPRINT, SYLVARES, SYLVAROAD, SYLVAROS, SYLVASOLV, SYLVATAC, SYLVATAL, SYLVATRAXX, TER-SET, UNICLEAR, UNIDYME, UNIFLEX, UNI-REZ, UNI-TAC, and ZONATAC are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2023 Kraton Corporation

Revision information

Product and Company Identification: Product and Company Identification

Handling and storage: Precautions for safe handling

Other information, including date of preparation or last revision: Disclaimer