

Version #: 8,0

Issue date: 02-July-2013

Revision date: 22-November-2023

Supersedes date: 03-August-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|---|------------------------------|
| Trade name or designation of the mixture | SYLVAROS™ DRS 731 |
| Registration number | - |
| UFI: | Germany: 5YX0-70AF-U001-JKTM |
| Synonyms | None. |
| SDS number | 8802 |
| Product code | 200000000349 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|-----------------------------|---|
| Identified uses | Industrial uses: Uses of substances as such or in preparations at industrial sites. Formulation [mixing] of preparations and/or re-packaging (excluding alloys). Manufacture of substance. Formulation of preparations. Distribution of substance. Use as an intermediate. Uses in coatings. Use in laboratories. Polymer production. Polymer processing. Rubber production and processing. Use as a fuel. Manufacture of paper and paper products. |
| Uses advised against | None known. |

1.3. Details of the supplier of the safety data sheet

| | |
|----------------------|--|
| Company name | Kraton Chemical B.V. |
| Address | Transistorstraat 16, 1322 CE Almere, The Netherlands |
| Phone | +31 36 546 2800 |
| Email address | regulatory.eu@kraton.com |

1.4. Emergency telephone number

| | |
|---|---|
| General in EU | 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Austria National Poisons Information Centre | +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Belgium National Poisons Control Centre | 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Bulgaria National Toxicological Information Centre | +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Croatia Poisons Information Centre | +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.) |
| Cyprus Poison Centre | 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Czech Republic National Poisons Information Centre | +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.) |
| Denmark National Poisons Control Centre | +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Estonia National Poisons Information Centre | 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.) |
| Finland National Poison Information Centre | (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| France National Poisons Control Centre | ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |

| | |
|---|---|
| Greece Poison Information Centre telephone number | (0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Hungary National Emergency Phone Number | +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Iceland Poison Centre | (+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Latvia Emergency medical aid | 113 |
| Latvia Poison and Drug Information Centre | +371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Lithuania Neatidėliotina informacija apsinuodijus | +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.) |
| Malta Accident and Emergency Department | 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.) |
| Netherlands National Poisons Information Centre (NVIC) | NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications) |
| Norway Norwegian Poison Information Centre | 22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Portugal Poison Centre | 800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Romania Biroul RSI si Informare Toxicologica | 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.) |
| Slovakia National Toxicological Information Centre | +421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Spain Toxicology Information Service | + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Sweden National Poison Information Centre | 112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |
| Switzerland Tox Info Suisse | 145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Serious eye damage/eye irritation

Category 2

H319 - Causes serious eye irritation.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Resin acids and Rosin acids, sodium salts

Hazard pictograms



Signal word

Warning

Hazard statements

H319

Causes serious eye irritation.

Precautionary statements

Prevention

P264 Wash thoroughly after handling.
P280 Wear eye protection/face protection.

Response

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage Not available.

Disposal Not available.

Supplemental label information 70 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | Index No. | Notes |
|---|-------|-------------------------|--|-----------|-------|
| Resin acids and Rosin acids, sodium salts | 60-70 | 61790-51-0 263-144-5 | 01-2119486963-21-0008 01-2119486963-21-0001 | - | |
| Classification: Eye Irrit. 2;H319 | | | | | |
| Other components below reportable levels | 30 | | | | |

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures Wear suitable protective equipment. Use water spray to cool unopened containers.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear appropriate personal protective equipment.

For emergency responders Keep unnecessary personnel away.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Avoid contact with eyes. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

7.2. Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Keep containers closed when not in use. Store at ambient temperature and atmospheric pressure.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

| Components | Value | Assessment factor | Notes |
|--|--------------------|-------------------|------------------------|
| Resin acids and Rosin acids, sodium salts (CAS 61790-51-0) | | | |
| Long-term, Systemic, Dermal | 1,065 mg/kg bw/day | 200 | Repeated dose toxicity |
| Long-term, Systemic, Oral | 1,065 mg/kg bw/day | 200 | Repeated dose toxicity |

Workers

| Components | Value | Assessment factor | Notes |
|--|----------------------|-------------------|------------------------|
| Resin acids and Rosin acids, sodium salts (CAS 61790-51-0) | | | |
| Long-term, Local, Inhalation | 10 mg/m ³ | | |
| Long-term, Systemic, Dermal | 2,131 mg/kg bw/day | 100 | Repeated dose toxicity |

Predicted no effect concentrations (PNECs)

| Components | Value | Assessment factor | Notes |
|--|-------------|-------------------|-------|
| Resin acids and Rosin acids, sodium salts (CAS 61790-51-0) | | | |
| Freshwater | 0,002 mg/l | 1000 | |
| Marine water | 0 mg/l | 10000 | |
| Sediment (freshwater) | 0,007 mg/kg | | |
| Sediment (marine water) | 0,001 mg/kg | | |
| Soil | 0 mg/kg | | |
| STP | 1000 mg/l | 10 | |

Exposure guidelines Occupational Exposure Limits are not relevant to the current physical form of the product.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

| | |
|--|--|
| General information | Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. |
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| - Hand protection | Wear appropriate chemical resistant gloves. When handling hot material, use heat resistant gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Wear suitable gloves tested to EN374. Recommended gloves include rubber, neoprene, nitrile or viton. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness should be typically greater than 0.35 mm. This recommendation is advisory only. It may not be appropriate for all workplaces. It should not be construed as offering an approval for any specific use scenario. A hazard assessment should be conducted prior to use to ensure suitability of gloves for specific work environments and processes. |
| - Other | Wear suitable protective clothing. |
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| Hygiene measures | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eye wash fountain and emergency showers are recommended. |
| Environmental exposure controls | Environmental manager must be informed of all major releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | Liquid. |
| Form | Paste. |
| Colour | Amber. |
| Odour | Mild. |
| Melting point/freezing point | Not available. |
| Boiling point or initial boiling point and boiling range | 100 °C (212 °F) (Water) 99,97 °C (211,95 °F) estimated |
| Flammability | Not available. |
| Flash point | >93,9 °C (>201,0 °F) estimated |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| pH | 9,6 at 20°C |
| Kinematic viscosity | Not available. |
| Solubility | |
| Solubility (water) | Soluble |
| Partition coefficient (n-octanol/water) (log value) | Not available. |
| Vapour pressure | 18 mm Hg at 20°C (water) |
| Density and/or relative density | |
| Density | 800,00 kg/m ³ at 20°C |
| Relative density | 0,8 at 25°C/25°C (water=1) |
| Vapour density | 0,6 (air=1) (water) |
| Particle characteristics | Not available. |

9.2. Other information

| | |
|--|---|
| 9.2.1. Information with regard to physical hazard classes | No relevant additional information available. |
|--|---|

9.2.2. Other safety characteristics

| | |
|-----------------------------------|-----------------------------------|
| Chemical family | Rosin Soap |
| Evaporation rate | 0,3 (n-BuAc=1) (water) |
| Flammability (temperature) | Non flammable. |
| Percent volatile | > 30 - < 40 % by weight (water) |
| Specific gravity | 0,8 at 20°C/20°C (water=1) |
| Viscosity | 1000 cP Cone and Plate at 60°C |
| Weighted solids | > 69 - < 71 ASTM D890 % by weight |

SECTION 10: Stability and reactivity

| | |
|---|---|
| 10.1. Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| 10.2. Chemical stability | Material is stable under normal conditions. |
| 10.3. Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| 10.4. Conditions to avoid | Strong oxidising agents. Contact with incompatible materials. |
| 10.5. Incompatible materials | Strong oxidising agents. |
| 10.6. Hazardous decomposition products | Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion. |

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

| | |
|---|---|
| Inhalation | No adverse effects due to inhalation are expected. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Causes serious eye irritation. |
| Resin acids and Rosin acids, sodium salts | Irritation Corrosion - Eye, May cause eye irritation.; Data is for similar product.; OECD 405 Result: Positive Species: New Zealand white rabbit Organ: Eye Observation Period: 7 d |
| Ingestion | May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. |

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Components | Species | Test Results |
|--|--------------------|--|
| Resin acids and Rosin acids, sodium salts (CAS 61790-51-0) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rat | > 2000 mg/kg, 24 Hours |
| | Sprague-Dawley rat | > 2000 mg/kg At this dose no death occurred.; Data is for similar product.; OECD 402 |
| Oral | | |
| LD50 | Rat | 1000 - 2000 mg/kg |
| | Sprague-Dawley rat | > 2000 mg/kg At this dose no death occurred.; Data is for similar product.; OECD 420 |
| Subchronic | | |
| Oral | | |
| NOAEL | Rat | 600 mg/kg/day, 90 d Data is for similar product.; |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Corrosivity

Resin acids and Rosin acids, sodium salts

Irritation Corrosion - Skin, No skin irritation.; Data is for similar product.; OECD 404

Result: Negative

Species: New Zealand white rabbit

Organ: Skin

Observation Period: 14 d

Serious eye damage/eye irritation

Causes serious eye irritation.

Eye contact

Resin acids and Rosin acids, sodium salts

Irritation Corrosion - Eye, May cause eye irritation.; Data is for similar product.; OECD 405

Result: Positive

Species: New Zealand white rabbit

Organ: Eye

Observation Period: 7 d

Respiratory sensitisation

Due to partial or complete lack of data the classification is not possible.

Skin sensitisation

Based on available data, the classification criteria are not met.

Skin Sensitisation

Resin acids and Rosin acids, sodium salts

Local Lymph Node Assay - Lowest Concentration Producing Reaction, Not a skin sensitizer.; Data is for similar product.; OECD 429

Result: Negative

Species: Mouse

Organ: Skin

Notes: SI<3;

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Resin acids and Rosin acids, sodium salts

Germ Cell Mutagenicity: Ames, Data is for similar product.; OECD 471

Result: Negative

Species: Salmonella typhimurium

Germ Cell Mutagenicity: Chromosom, Data is for similar product.; OECD 473

Result: Negative

Species: Human

In vitro gene mutation study in mammalian cells, Data is for similar product.; OECD 476

Result: Negative

Species: Mouse

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information

No information available.

11.2. Information on other hazards**Endocrine disrupting properties**

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information

Not available.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

| Components | Species | | Test Results |
|--|---------|---------------|--|
| Resin acids and Rosin acids, sodium salts (CAS 61790-51-0) | | | |
| Aquatic | | | |
| Crustacea | LC50 | Daphnia | 1,6 mg/l, 48 hr Data is for similar product.; OECD 202 |
| Fish | LC50 | Danio (Danio) | 5,4 mg/l, 96 hr OECD 203 |

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability

Biodegradability

Percent Degradation (Aerobic Biodegradation)

| | |
|---|---|
| Resin acids and Rosin acids, sodium salts | 71 %, OECD 301D Result: Readily biodegradable Species: Activated sewage sludge Test Duration: 28 d |
|---|---|

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

| | |
|---|----------------|
| Resin acids and Rosin acids, sodium salts | 4,769, at 20°C |
|---|----------------|

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|-------------------------------------|--|
| Residual waste | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |
| EU waste code | The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Disposal methods/information | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Special precautions | Dispose in accordance with all applicable regulations. |

SECTION 14: Transport information

ADR

| | |
|---|-----------------------------------|
| 14.1. UN number | Not regulated as dangerous goods. |
| 14.2. UN proper shipping name | Not regulated as dangerous goods. |
| 14.3. Transport hazard class(es) | |
| Class | Not assigned. |
| Subsidiary risk | - |
| Hazard No. (ADR) | Not assigned. |
| Tunnel restriction code | Not assigned. |
| 14.4. Packing group | Not assigned. |
| 14.5. Environmental hazards | No. |
| 14.6. Special precautions for user | Not assigned. |

RID

| | |
|---|-----------------------------------|
| 14.1. UN number | Not regulated as dangerous goods. |
| 14.2. UN proper shipping name | Not regulated as dangerous goods. |
| 14.3. Transport hazard class(es) | |
| Class | Not assigned. |
| Subsidiary risk | - |
| 14.4. Packing group | Not assigned. |

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

ADN

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping name Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping name Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IMDG

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping name Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards

Marine pollutant No.

EmS Not assigned.

14.6. Special precautions Not assigned.

for user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

Germany: 5YX0-70AF-U001-JKTM

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

Water hazard class

AwSV

WGK1

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H319 Causes serious eye irritation.

Revision information

Product and Company Identification: EU Poison Centre

Training information

Follow training instructions when handling this material.

Disclaimer

KRATON CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information set forth in this document, as of the date of this document, is based on present knowledge, obtained from reliable sources and made to our reasonable ability and in good faith. Such information is made without any warranty or guarantee whatsoever, and shall establish no legal duty or responsibility on the part of the author(s), their employer or its affiliates. The information given is designed only as guidance and its completeness is not guaranteed. The information is not a guarantee of any specific product properties, features, qualities or specifications.

The information relates only to the specific product designated as shipped, and may not be valid for such product used in combination with any other materials or products, or in any process, unless expressly specified in this document. Nothing set forth in this document shall be construed as a recommendation or license to use any product in conflict with, or as claimed by, any existing patents rights. The user alone must finally determine whether a contemplated use of a product will infringe any such patents. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities are in compliance with all Local, Federal and International Legislation and Local Permits.

We, for ourselves and on behalf of our affiliates, expressly disclaim any and all liability for any damages or injuries arising out of any activities relating in any way to the information set forth in this document. Due to the proliferation of sources for information, we are not and cannot be responsible for SDSs obtained from any other source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

*KRATON, the KRATON logo, the "Green Super Drop" logo, 1101, ABIETA, AQUATAC, BiaXam, BI-THIN, CENTURY, CENWAX, CirKular+, ELEXAR, ELLAMERA, E-LEXAR, HiMA, IMSS, IPD, NEXAR, PER-SUST, PriMul, RAD-THICK, REFLECTAID, REvolution, SYLFAT, SYLVABIND, SYLVABLEND, SYLVACLEAR, SYLVACOTE, SYLVADERM, SYLVAFUEL, SYLVAGEL, SYLVAGUM, SYLVALITE, SYLVAMIN, SYLVAPINE, SYLVAPRINT, SYLVARES, SYLVAROAD, SYLVAROS, SYLVASOLV, SYLVATAC, SYLVATAL, SYLVATRAXX, TER-SET, UNICLEAR, UNIDYME, UNIFLEX, UNI-REZ, UNI-TAC, and ZONATAC are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2023 Kraton Corporation

Annex to the extended Safety Data Sheet (eSDS)

Table of contents

| | |
|--|----|
| 1. ES Manufacture of substance (SU3, SU8, SU9, ERC1, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 13 |
| 2. ES Formulation of preparations (SU3, ERC2, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 16 |
| 3. ES Distribution of substance (SU8, SU9, SU0, SU3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 19 |
| 4. ES Intermediate (SU8, SU9, SU0, SU3, ERC6a, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 22 |
| 5. ES Coating. (SU0, SU3, ERC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 25 |
| 6. ES Laboratory use (SU0, SU3, ERC4, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 28 |
| 7. ES Polymerization (Bulk and batch) (SU10, SU0, SU3, ERC4, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 31 |
| 8. ES Polymer preparations and compounds (SU10, SU0, SU3, ERC4, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 34 |
| 9. ES Rubber production and processing (SU10, SU0, SU3, ERC4, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 37 |
| 10. ES Fuels (SU0, SU3, ERC7, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 40 |
| 11. ES Paper articles (SU6b, SU10, ERC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 43 |
| 12. ES Coating. (SU0, SU22, SU21, PC1, PC4, PC8, PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34, ERC8c, ERC8f, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 46 |
| 13. ES Polymer preparations and compounds (SU0, SU22, ERC8a, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 49 |
| 14. ES Fuels (SU0, SU22, SU21, ERC9a, ERC9b, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 52 |
| 15. ES Laboratory use (SU0, SU22, ERC8d, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15) | 55 |

1 - Exposure Scenario Worker

1. Manufacture of substance

List of use descriptors

Sector(s) of Use SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals

Name of contributing environmental scenario and corresponding ERC Manufacture of substance
ERC1: Manufacture of substances

List of names of contributing worker scenarios and corresponding PROCs Manufacture of substance
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Manufacture of substance

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 1,285 e5 tons/year
Regional use tonnage (tons/year): 12900 tons/year
Fraction of Regional tonnage used locally: 1
Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|--------|-------------|---------|
| | | Air | Soil | Water | |
| | 300 | 0,000042 | 0,0001 | 0,000000089 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.
Soil Not available.
Water Not available.
Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.
Discharge rate 2000
Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Manufacture of substance

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 4,14E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,38E-05 mg/l | 0,00851 | Used EUSES model. | |
| marine water | 1,37E-06 mg/l | 0,00845 | Used EUSES model. | |
| freshwater sediment | 1,53E-03 mg/kg wet weight | 0,993 | Used EUSES model. | |
| marine sediment | 1,52E-04 mg/kg wet weight | 0,987 | Used EUSES model. | |
| soil | 3,92E-04 mg/kg wet weight | 0,987 | Used EUSES model. | |
| STP | 1,29E-04 mg/l | 0,000000127 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

2 - Exposure Scenario Worker

1. Formulation of preparations

List of use descriptors

| | |
|---|---|
| Sector(s) of Use | SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Formulation of preparations ERC2: Formulation of preparations |
| List of names of contributing worker scenarios and corresponding PROCs | Formulation of preparations PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Formulation of preparations

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|-----------------|
| Annual amount used in the EU | 54000 tons/year |
| Regional use tonnage (tons/year): | 5400 tons/year |
| Fraction of Regional tonnage used locally: | 1 |
| Emission days (days/year): | 220 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|--------|-------------|---------|
| | | Air | Soil | Water | |
| | 220 | 0,0001 | 0,0001 | 0,000000157 | |

Risk management measures (RMM)

| | |
|---|--|
| Technical conditions and measures at process level (source) to prevent release | Common practices vary across sites thus conservative process release estimates used. |
|---|--|

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

| | |
|---|---|
| Organisational measures to prevent/limit release from site | Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater. |
|---|---|

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

| | |
|---------------------------------|---|
| Suitable waste treatment | Dispose of waste product or used containers according to local regulations. |
| Treatment effectiveness | Not available. |

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Formulation of preparations

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 4,14E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,03E-05 mg/l | 0,00646 | Used EUSES model. | |
| marine water | 1,03E-06 mg/l | 0,00641 | Used EUSES model. | |
| freshwater sediment | 1,15E-03 mg/kg wet weight | 0,754 | Used EUSES model. | |
| marine sediment | 1,14E-04 mg/kg wet weight | 0,748 | Used EUSES model. | |
| soil | 3,92E-04 mg/kg wet weight | 0,987 | Used EUSES model. | |
| STP | 9,45E-05 mg/l | 0,0000000945 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

3 - Exposure Scenario Worker

1. Distribution of substance

List of use descriptors

Sector(s) of Use

SU8: Manufacture of bulk, large scale chemicals (including petroleum products). SU9: Manufacture of fine chemicals. SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites.

Name of contributing environmental scenario and corresponding ERC

Distribution of substance
 ERC4: Industrial use of processing aids in processes and products, not becoming part of article 5.
 ERC5: Industrial use resulting in inclusion into or onto a matrix
 .
 ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)
 .
 ERC6b: Industrial use of reactive processing aids
 .
 ERC6c: Industrial use of monomers for manufacture of thermoplastics
 .
 ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers
 .
 ERC7: Industrial use of substances in closed systems
 .

List of names of contributing worker scenarios and corresponding PROCs

Distribution of substance
 PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Distribution of substance

Product characteristics

Concentration of the substance in a mixture

Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state

solid

Amounts used

Annual amount used in the EU 19300 tons/year
 Regional use tonnage (tons/year): 1930 tons/year
 Fraction of Regional tonnage used locally: 0,002
 Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10
 Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|---------|---------|---------|
| | | Air | Soil | Water | |
| | 300 | 0,00001 | 0,00001 | 0,00001 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.
 Soil Not available.
 Water Not available.
 Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.
Discharge rate 2000
Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.
Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Distribution of substance

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product solid
vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. wash off any skin contamination immediately. provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,11E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,39E-06 mg/l | 0,000869 | Used EUSES model. | |
| marine water | 1,31E-07 mg/l | 0,000817 | Used EUSES model. | |
| freshwater sediment | 1,54E-04 mg/kg wet weight | 0,101 | Used EUSES model. | |

| | | | |
|-----------------|---------------------------------|--------------|-------------------|
| marine sediment | 1,45E-05 mg/kg wet weight | 0,0953 | Used EUSES model. |
| soil | 3,31E-06 mg/kg wet weight | 0,00835 | Used EUSES model. |
| STP | 4,30E-06 mg/l | 0,0000000043 | Used EUSES model. |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

4 - Exposure Scenario Worker

1. Intermediate

List of use descriptors

Sector(s) of Use

SU8: Manufacture of bulk, large scale chemicals (including petroleum products). SU9: Manufacture of fine chemicals. SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites.

Name of contributing environmental scenario and corresponding ERC

Intermediate
ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)
.

List of names of contributing worker scenarios and corresponding PROCs

Intermediate
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Intermediate

Product characteristics

Concentration of the substance in a mixture

Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state

solid

Amounts used

Annual amount used in the EU 83500 tons/year

Regional use tonnage (tons/year): 8350 tons/year

Fraction of Regional tonnage used locally: 1

Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days | Emission factors | | | Remarks |
|------|---------------|------------------|-------|------------|---------|
| | (days/year) | Air | Soil | Water | |
| | 300 | 0,00002 | 0,001 | 0,00000013 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.

Soil Not available.

Water Not available.

Sediment Not available.

Organisational measures to prevent/limit release from site

Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

Discharge rate 2000

Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Intermediate

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 1,30E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,30E-05 mg/l | 0,00811 | Used EUSES model. | |
| marine water | 1,29E-06 mg/l | 0,00806 | Used EUSES model. | |
| freshwater sediment | 1,44E-03 mg/kg wet weight | 0,946 | Used EUSES model. | |
| marine sediment | 1,43E-04 mg/kg wet weight | 0,94 | Used EUSES model. | |
| soil | 1,24E-04 mg/kg wet weight | 0,312 | Used EUSES model. | |
| STP | 1,21E-04 mg/l | 0,000000121 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

5 - Exposure Scenario Worker

1. Coating.

List of use descriptors

| | |
|---|--|
| Sector(s) of Use | SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Coating. ERC5: Industrial use resulting in inclusion into or onto a matrix |
| List of names of contributing worker scenarios and corresponding PROCs | Coating. PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Coating.

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|----------------|
| Annual amount used in the EU | 6000 tons/year |
| Regional use tonnage (tons/year): | 600 tons/year |
| Fraction of Regional tonnage used locally: | 1 |
| Emission days (days/year): | 220 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|------|-------|---------|
| | | Air | Soil | Water | |
| | 220 | 0,0009 | 0 | 0 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

| | |
|---------------------------------|---|
| Suitable waste treatment | Dispose of waste product or used containers according to local regulations. |
|---------------------------------|---|

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Coating.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 4,14E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 9,63E-07 mg/l | 0,000602 | Used EUSES model. | |
| marine water | 8,81E-08 mg/l | 0,00055 | Used EUSES model. | |
| freshwater sediment | 1,07E-04 mg/kg wet weight | 0,0703 | Used EUSES model. | |
| marine sediment | 9,77E-06 mg/kg wet weight | 0,0642 | Used EUSES model. | |
| soil | 3,92E-04 mg/kg wet weight | 0,987 | Used EUSES model. | |
| STP | 0 mg/l | 0 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

6 - Exposure Scenario Worker

1. Laboratory use

List of use descriptors

| | |
|---|--|
| Sector(s) of Use | SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Laboratory use ERC4: Industrial use of processing aids in processes and products, not becoming part of articles. |
| List of names of contributing worker scenarios and corresponding PROCs | Laboratory use PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Laboratory use

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|-------------------|
| Annual amount used in the EU | 0,0103 tons/year |
| Regional use tonnage (tons/year): | 0,00103 tons/year |
| Fraction of Regional tonnage used locally: | 0,1 |
| Emission days (days/year): | 20 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|--------|-------|---------|
| | | Air | Soil | Water | |
| | 20 | 0,025 | 0,0001 | 0,02 | |

Risk management measures (RMM)

| | |
|---|--|
| Technical conditions and measures at process level (source) to prevent release | Common practices vary across sites thus conservative process release estimates used. |
|---|--|

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

| | |
|---|---|
| Organisational measures to prevent/limit release from site | Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater. |
|---|---|

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

| | |
|---------------------------------|---|
| Suitable waste treatment | Dispose of waste product or used containers according to local regulations. |
|---------------------------------|---|

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Laboratory use

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,08E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,30E-06 mg/l | 0,000815 | Used EUSES model. | |
| marine water | 5,98E-07 mg/l | 0,00374 | Used EUSES model. | |
| freshwater sediment | 1,45E-04 mg/kg wet weight | 0,0951 | Used EUSES model. | |
| marine sediment | 6,64E-05 mg/kg wet weight | 0,436 | Used EUSES model. | |
| soil | 6,05E-05 mg/kg wet weight | 0,191 | Used EUSES model. | |
| STP | 3,44E-06 mg/l | 0,0000000344 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

7 - Exposure Scenario Worker

1. Polymerization (Bulk and batch)

List of use descriptors

| | |
|---|---|
| Sector(s) of Use | SU10: Formulation [mixing] of preparations and/or re-packaging. SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Polymerization (Bulk and batch) ERC4: Industrial use of processing aids in processes and products, not becoming part of articles. |
| List of names of contributing worker scenarios and corresponding PROCs | Polymerization (Bulk and batch) PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Polymerization (Bulk and batch)

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|---------------|
| Annual amount used in the EU | 120 tons/year |
| Regional use tonnage (tons/year): | 12 tons/year |
| Fraction of Regional tonnage used locally: | 1 |
| Emission days (days/year): | 300 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|--------|----------|---------|
| | | Air | Soil | Water | |
| | 300 | 0,002 | 0,0001 | 0,000095 | |

Risk management measures (RMM)

| | |
|---|--|
| Technical conditions and measures at process level (source) to prevent release | Common practices vary across sites thus conservative process release estimates used. |
|---|--|

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

| | |
|---|---|
| Organisational measures to prevent/limit release from site | Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater. |
|---|---|

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

| | |
|---------------------------------|---|
| Suitable waste treatment | Dispose of waste product or used containers according to local regulations. |
|---------------------------------|---|

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Polymerization (Bulk and batch)

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 2,14E-05 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,36E-05 mg/l | 0,00852 | Used EUSES model. | |
| marine water | 1,35E-06 mg/l | 0,00846 | Used EUSES model. | |
| freshwater sediment | 1,51E-03 mg/kg wet weight | 0,994 | Used EUSES model. | |
| marine sediment | 1,50E-04 mg/kg wet weight | 0,988 | Used EUSES model. | |
| soil | 2,08E-05 mg/kg wet weight | 0,0523 | Used EUSES model. | |
| STP | 1,28E-04 mg/l | 0,000000128 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

8 - Exposure Scenario Worker

1. Polymer preparations and compounds

List of use descriptors

| | |
|---|--|
| Sector(s) of Use | SU10: Formulation [mixing] of preparations and/or re-packaging. SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Polymer preparations and compounds ERC4: Industrial use of processing aids in processes and products, not becoming part of articles. |
| List of names of contributing worker scenarios and corresponding PROCs | Polymer preparations and compounds PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Polymer preparations and compounds

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|---------------|
| Annual amount used in the EU | 120 tons/year |
| Regional use tonnage (tons/year): | 12 tons/year |
| Fraction of Regional tonnage used locally: | 1 |
| Emission days (days/year): | 300 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|---------|-------|---------|
| | | Air | Soil | Water | |
| | 300 | 0,02 | 0,00001 | 0 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment**Suitable waste treatment** Dispose of waste product or used containers according to local regulations.**Treatment effectiveness** Not available.**Conditions and measures related to external recovery of waste****Fraction of used amount transferred to external waste treatment****Suitable recover operations** External recovery and recycling of waste should comply with applicable local and/or national regulations.**2.2.1. Contributing scenario controlling worker exposure for Polymer preparations and compounds****Product characteristics****Concentration of the substance in a mixture** Covers percentage substance in the product up to 100 % (unless stated differently).**Physical form of the product** solid**vapour pressure** Not available.**Amounts used**

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management**Other given operational conditions affecting workers exposure**

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)**Technical conditions and measures to control dispersion from source towards the worker** Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.**Organizational measures to prevent/limit releases, dispersion and exposure** Not available.**Conditions and measures related to personal protection, hygiene and health evaluations** Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.**3. Exposure Estimation****Environment**

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 1,86E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 9,63E-07 mg/l | 0,000602 | Used EUSES model. | |
| marine water | 8,81E-08 mg/l | 0,00055 | Used EUSES model. | |
| freshwater sediment | 1,07E-04 mg/kg wet weight | 0,0703 | Used EUSES model. | |
| marine sediment | 9,77E-06 mg/kg wet weight | 0,0642 | Used EUSES model. | |
| soil | 1,77E-04 mg/kg wet weight | 0,445 | Used EUSES model. | |
| STP | 0 mg/l | 0 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

9 - Exposure Scenario Worker

1. Rubber production and processing

List of use descriptors

| | |
|---|--|
| Sector(s) of Use | SU10: Formulation [mixing] of preparations and/or re-packaging. SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites. |
| Name of contributing environmental scenario and corresponding ERC | Rubber production and processing ERC4: Industrial use of processing aids in processes and products, not becoming part of articles. |
| List of names of contributing worker scenarios and corresponding PROCs | Rubber production and processing PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent |

2.1.1. Contributing scenario controlling environmental exposure for Rubber production and processing

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical state | solid |

Amounts used

| | |
|---|---------------|
| Annual amount used in the EU | 400 tons/year |
| Regional use tonnage (tons/year): | 40 tons/year |
| Fraction of Regional tonnage used locally: | 1 |
| Emission days (days/year): | 300 |

Environment factors not influenced by risk management

| | |
|--|-----|
| Local freshwater dilution factor: | 10 |
| Local marine water dilution factor: | 100 |

Other given operational conditions affecting environmental exposure

| Type | Emission days | | Emission factors | | | Remarks |
|------|---------------|------|------------------|----------|--|---------|
| | (days/year) | Air | Soil | Water | | |
| | 300 | 0,01 | 0,0001 | 0,000028 | | |

Risk management measures (RMM)

| | |
|---|--|
| Technical conditions and measures at process level (source) to prevent release | Common practices vary across sites thus conservative process release estimates used. |
|---|--|

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

| | |
|-----------------|----------------|
| Air | Not available. |
| Soil | Not available. |
| Water | Not available. |
| Sediment | Not available. |

| | |
|---|---|
| Organisational measures to prevent/limit release from site | Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater. |
|---|---|

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

| | |
|-----------------------------------|---------------------------------|
| Type | Municipal STP. Onsite STP. |
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Rubber production and processing

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,07E-04 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,33E-05 mg/l | 0,00834 | Used EUSES model. | |
| marine water | 1,33E-06 mg/l | 0,00829 | Used EUSES model. | |
| freshwater sediment | 1,48E-03 mg/kg wet weight | 0,973 | Used EUSES model. | |
| marine sediment | 1,47E-04 mg/kg wet weight | 0,967 | Used EUSES model. | |
| soil | 2,91E-04 mg/kg wet weight | 0,733 | Used EUSES model. | |
| STP | 1,25E-04 mg/l | 0,000000125 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

10 - Exposure Scenario Worker

1. Fuels

List of use descriptors

Sector(s) of Use SU0: Other: SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites.

Name of contributing environmental scenario and corresponding ERC

Fuels
ERC7: Industrial use of substances in closed systems

List of names of contributing worker scenarios and corresponding PROCs

Fuels
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Fuels

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 1 tons/year

Regional use tonnage (tons/year): 0,1 tons/year

Fraction of Regional tonnage used locally: 1

Emission days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|------|---------|---------|
| | | Air | Soil | Water | |
| | 300 | 0,00025 | 0 | 0,00001 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.

Soil Not available.

Water Not available.

Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

Discharge rate 2000

Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Fuels

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,09E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 9,75E-07 mg/l | 0,000609 | Used EUSES model. | |
| marine water | 1,05E-07 mg/l | 0,000654 | Used EUSES model. | |
| freshwater sediment | 1,08E-04 mg/kg wet weight | 0,0711 | Used EUSES model. | |
| marine sediment | 1,16E-05 mg/kg wet weight | 0,0763 | Used EUSES model. | |
| soil | 5,16E-06 mg/kg wet weight | 0,0142 | Used EUSES model. | |
| STP | 1,12E-07 mg/l | 0,00000000112 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

11 - Exposure Scenario Worker

1. Paper articles

List of use descriptors

Sector(s) of Use SU6b: Manufacture of pulp, paper and paper products. SU10: Formulation [mixing] of preparations and/or re-packaging

Name of contributing environmental scenario and corresponding ERC

Paper articles
ERC5: Industrial use resulting in inclusion into or onto a matrix

List of names of contributing worker scenarios and corresponding PROCs

Paper articles
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Paper articles

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 1 tons/year

Regional use tonnage (tons/year): 0,1 tons/year

Fraction of Regional tonnage used locally: 1

Emission days (days/year): 220

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|------|-------|---------|
| | | Air | Soil | Water | |
| | 220 | 0,009 | 0 | 0 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.

Soil Not available.

Water Not available.

Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

Discharge rate 2000

Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Paper articles

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,77E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 9,63E-07 mg/l | 0,000602 | Used EUSES model. | |
| marine water | 8,81E-08 mg/l | 0,000515 | Used EUSES model. | |
| freshwater sediment | 1,07E-04 mg/kg wet weight | 0,0702 | Used EUSES model. | |
| marine sediment | 9,78E-06 mg/kg wet weight | 0,0642 | Used EUSES model. | |
| soil | 3,93E-06 mg/kg wet weight | 0,0099 | Used EUSES model. | |
| STP | 0 mg/l | 0 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

12 - Exposure Scenario Worker

1. Coating.

List of use descriptors

Sector(s) of Use SU0: Other: SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen). SU21: Consumer uses

Product categories [PC]: PC1: Adhesives, sealants. PC4: Anti-freeze and de-icing products. PC8: Biocidal products. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC9c: Finger paints. PC15: Non-metal-surface treatment products. PC18: Ink and toners. PC23: Leather tanning, dye, finishing, impregnation and care products. PC24: Lubricants, greases, release products. PC31: Polishes and wax blends. PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids

Name of contributing environmental scenario and corresponding ERC

Coating.
ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix
.
ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix
.

List of names of contributing worker scenarios and corresponding PROCs

Coating.
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Coating.

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 4000 tons/year
Regional use tonnage (tons/year): 400 tons/year
Fraction of Regional tonnage used locally: 0,002
Emission days (days/year): 365

Environment factors not influenced by risk management

Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days | | Emission factors | | | Remarks |
|------|---------------|-----|------------------|---------|--|---------|
| | (days/year) | Air | Soil | Water | | |
| | 365 | 0 | 0 | 0,00011 | | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.
Soil Not available.
Water Not available.
Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

| | |
|-----------------------------------|---------------------------------|
| Discharge rate | 2000 |
| Sludge treatment technique | Do not use sludge as fertiliser |

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

| | |
|---------------------------------|---|
| Suitable waste treatment | Dispose of waste product or used containers according to local regulations. |
| Treatment effectiveness | Not available. |

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

| | |
|------------------------------------|---|
| Suitable recover operations | External recovery and recycling of waste should comply with applicable local and/or national regulations. |
|------------------------------------|---|

2.2.1. Contributing scenario controlling worker exposure for Coating.

Product characteristics

| | |
|--|---|
| Concentration of the substance in a mixture | Covers percentage substance in the product up to 100 % (unless stated differently). |
| Physical form of the product | solid |
| vapour pressure | Not available. |

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

| | |
|---|--|
| Technical conditions and measures to control dispersion from source towards the worker | Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. |
| Organizational measures to prevent/limit releases, dispersion and exposure | Not available. |
| Conditions and measures related to personal protection, hygiene and health evaluations | Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. |

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,09E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,76E-06 mg/l | 0,0011 | Used EUSES model. | |
| marine water | 1,28E-06 mg/l | 0,00802 | Used EUSES model. | |
| freshwater sediment | 1,96E-04 mg/kg wet weight | 0,129 | Used EUSES model. | |
| marine sediment | 1,42E-04 mg/kg wet weight | 0,936 | Used EUSES model. | |

| | | | |
|------|---------------------------------|---------------|-------------------|
| soil | 1,37E-04 mg/kg wet weight | 0,436 | Used EUSES model. |
| STP | 8,06E-06 mg/l | 0,00000000806 | Used EUSES model. |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

13 - Exposure Scenario Worker

1. Polymer preparations and compounds

List of use descriptors

Sector(s) of Use SU0: Other: SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Name of contributing environmental scenario and corresponding ERC Polymer preparations and compounds
ERC8a: Wide dispersive indoor use of processing aids in open systems

List of names of contributing worker scenarios and corresponding PROCs Polymer preparations and compounds
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Polymer preparations and compounds

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 120 tons/year

Regional use tonnage (tons/year): 12 tons/year

Fraction of Regional tonnage used locally: 0,0005

Emission days (days/year): 365

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|------|-------|---------|
| | | Air | Soil | Water | |
| | 365 | 0,98 | 0,01 | 0,01 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.

Soil Not available.

Water Not available.

Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

Discharge rate 2000

Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Polymer preparations and compounds

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 7,57E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,51E-06 mg/l | 0,000944 | Used EUSES model. | |
| marine water | 9,07E-07 mg/l | 0,00567 | Used EUSES model. | |
| freshwater sediment | 1,68E-04 mg/kg wet weight | 0,11 | Used EUSES model. | |
| marine sediment | 1,01E-04 mg/kg wet weight | 0,661 | Used EUSES model. | |
| soil | 9,93E-05 mg/kg wet weight | 0,312 | Used EUSES model. | |
| STP | 5,52E-06 mg/l | 0,0000000552 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

14 - Exposure Scenario Worker

1. Fuels

List of use descriptors

Sector(s) of Use SU0: Other: SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen). SU21: Consumer uses

Name of contributing environmental scenario and corresponding ERC

Fuels
 ERC9a: Wide dispersive indoor use of substances in closed systems
 .
 ERC9b: Wide dispersive outdoor use of substances in closed systems
 .

List of names of contributing worker scenarios and corresponding PROCs

Fuels
 PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Fuels

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 1 tons/year
Regional use tonnage (tons/year): 0,1 tons/year
Fraction of Regional tonnage used locally: 0,0005
Emission days (days/year): 365

Environment factors not influenced by risk management

Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|---------|---------|---------|
| | | Air | Soil | Water | |
| | 365 | 0,0001 | 0,00001 | 0,00001 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.
Soil Not available.
Water Not available.
Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.
Discharge rate 2000
Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing scenario controlling worker exposure for Fuels

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,08E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 9,63E-07 mg/l | 0,000602 | Used EUSES model. | |
| marine water | 8,81E-08 mg/l | 0,00055 | Used EUSES model. | |
| freshwater sediment | 1,07E-04 mg/kg wet weight | 0,0703 | Used EUSES model. | |
| marine sediment | 9,77E-06 mg/kg wet weight | 0,0642 | Used EUSES model. | |
| soil | 3,28E-06 mg/kg wet weight | 0,00827 | Used EUSES model. | |
| STP | 4,60E-11 mg/l | 0,00000000000004 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.

15 - Exposure Scenario Use in laboratories; Professional

1. Laboratory use

List of use descriptors

Sector(s) of Use SU0: Other: SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Name of contributing environmental scenario and corresponding ERC Laboratory use
ERC8d: Wide dispersive outdoor use of processing aids in open systems

List of names of contributing worker scenarios and corresponding PROCs Laboratory use
PROC1: Use in closed process, no likelihood of exposure. PROC2: Use in closed, continuous process with occasional controlled exposure. PROC3: Use in closed batch process (synthesis or formulation). PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises. PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities. PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC15: Use as laboratory reagent

2.1.1. Contributing scenario controlling environmental exposure for Laboratory use

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical state solid

Amounts used

Annual amount used in the EU 1 tons/year

Regional use tonnage (tons/year): 0,1 tons/year

Fraction of Regional tonnage used locally: 0,0005

Emission days (days/year): 365

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure

| Type | Emission days (days/year) | Emission factors | | | Remarks |
|------|---------------------------|------------------|------|-------|---------|
| | | Air | Soil | Water | |
| | 365 | 0,5 | 0 | 0,5 | |

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air Not available.

Soil Not available.

Water Not available.

Sediment Not available.

Organisational measures to prevent/limit release from site Do not apply industrial sludge to natural soils. Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m3/d)

Type Municipal STP. Onsite STP.

Discharge rate 2000

Sludge treatment technique Do not use sludge as fertiliser

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment

Suitable waste treatment Dispose of waste product or used containers according to local regulations.

Treatment effectiveness Not available.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment

Suitable recover operations External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2.1. Contributing exposure scenario controlling use in laboratories; professional exposure for Laboratory use

Product characteristics

Concentration of the substance in a mixture Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product solid

vapour pressure Not available.

Amounts used

Not available.

Frequency and duration of use

Not available.

Human factors not influenced by risk management

Other given operational conditions affecting workers exposure

Not available.

Other relevant operational conditions

Not available.

Risk management measures (RMM)

Technical conditions and measures to control dispersion from source towards the worker Assumes a good basic standard of occupational hygiene is implemented. Ensure that splashes and spills are avoided by product design. Avoid contact with contaminated tools and objects. Clean equipment and the work area every day. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Organizational measures to prevent/limit releases, dispersion and exposure Not available.

Conditions and measures related to personal protection, hygiene and health evaluations Avoid direct eye contact with product, also via contamination on hands. Use suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Clear up spills immediately and dispose of waste safely. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

3. Exposure Estimation

Environment

| Compartment | PEC | RCR (PEC/PNEC) | Method | Remarks |
|---------------------|----------------------------|---------------------------------|-------------------|---------|
| Air. | 3,10E-06 mg/m ³ | The use is assessed to be safe. | Used EUSES model. | |
| freshwater | 1,19E-06 mg/l | 0,000744 | Used EUSES model. | |
| marine water | 4,29E-07 mg/l | 0,00268 | Used EUSES model. | |
| freshwater sediment | 1,32E-04 mg/kg wet weight | 0,0868 | Used EUSES model. | |
| marine sediment | 4,76E-05 mg/kg wet weight | 0,313 | Used EUSES model. | |
| soil | 4,15E-05 mg/kg wet weight | 0,13 | Used EUSES model. | |
| STP | 2,30E-06 mg/l | 0,0000000023 | Used EUSES model. | |

Health

Not available.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

The immediate downstream user is required to evaluate whether the risk management measures and operational conditions described in the ES fits to his use. Where other RMM / OC are adopted, user should then ensure that risks are managed to at least equivalent levels. This may be based on a set of determinants (and a suitable algorithm) which together ensure control of risk. Where relevant DU can use other methods, such as scaling, he needs to check whether he acts within the boundaries set by the information provided in the exposure scenario.