

1. Identification

Product identifier	Kraton™ FG Polymers (SEBS Maleated)
Other means of identification	
SDS number	14423
Product Code	FG1901, FG1924, FG1929
Synonyms	This SDS covers all alphanumeric suffixes for the following products. Suffixes designate location of manufacture, dusting agent, product form.
Recommended use	Industrial use
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
	CORPORATE OFFICE
Name	Kraton Corporation
Address	9950 Woodloch Forest Dr., Suite 2400 The Woodlands, TX 77380, USA
Telephone	+1 281 504 4700
	EUROPEAN CENTRAL OFFICE
Name	Kraton Polymers Nederland B.V.
Address	Transistorstraat 16 1322 CE Almere, The Netherlands
Telephone	+31 (0) 36 546 2846
Email address	Product.Safety@Kraton.com
Technical Support Line - International	+1 800 4 Kraton (572866) ; +1 281 504 4950
Technical Support Line - EU	+31 (0) 36 546 2800
Website	www.Kraton.com
CHEMTREC - Domestic:	+1 800 424 9300
CHEMTREC - International:	+1 703 527 3887
SGS ECLN:	+32 35 75 03 30

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	Not applicable.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Not applicable.

Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	Static charge accumulation potential. Vapors may accumulate in headspace when product is stored in closed containers. Exposure to vapors may cause mild skin, eye and respiratory irritation
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEBS Maleated		66070-58-4 (Maleate < 2% polymer)	<100

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. Prolonged contact may cause dryness of the skin.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. No specific antidotes are recommended.

5. Fire-fighting measures

Suitable extinguishing media	Water spray, dry chemical, carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Wear suitable protective equipment. Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Static charges generated by emptying package in or near flammable vapor may cause flash fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	If spilled, may cause a slipping hazard. Avoid dust formation. Wear appropriate personal protective equipment. Keep away from sources of ignition - No smoking. Ensure adequate ventilation.
Methods and materials for containment and cleaning up	Avoid the generation of dusts during clean-up. The product is immiscible with water and will spread on the water surface.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Minimize dust generation and accumulation. Avoid heat, sparks, open flames and other ignition sources. Do not smoke. Static electricity and formation of sparks must be prevented. Ground container and transfer equipment to eliminate static electric sparks. Maintain a fire watch if material reaches 280°C (536°F). Avoid contact with hot material. Do not breathe dust from this material. Observe good industrial hygiene practices.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Store indoor. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. To maintain product quality, do not store in heat or direct sunlight. Keep in a cool, well-ventilated place. Store in original tightly closed container. Keep containers closed when not in use. Store at ambient temperature and atmospheric pressure. Guard against dust accumulation of this material. Use care in handling/storage. Do not stack Flexible Intermediate Bulk Containers (FIBCs) or palletized bags. Avoid storage under pressure or at elevated temperatures to minimize particulate clustering. Do not store outside. Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight, and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletized bags or other package units. Indeed, polymer products may be dimensionally unstable under certain conditions.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)**

Additional components	Type	Value	Form
Organic Dust	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Talc	TWA	0.1 mg/m ³	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Additional components	Type	Value	Form
Talc	TWA	2 mg/m ³	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Additional components	Type	Value
Talc	IDLH	1000 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Additional components	Type	Value	Form
Talc	TWA	2 mg/m ³	Respirable.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Gloves are recommended for prolonged use. When handling hot material, use heat resistant gloves.

Other

Wear suitable protective clothing and gloves.

Respiratory protection

If ventilation is insufficient, suitable respiratory protection must be provided.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Solid.

Form

Dense Pellet.

Color

Yellow

Odor

Pungent

Odor threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	The product is not flammable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not applicable. Not applicable.
Explosive limit - lower (%) temperature	Not applicable.
Explosive limit - upper (%)	Not applicable. Not applicable.
Explosive limit - upper (%) temperature	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	> 0.88 - < 0.95 at 20°C
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Risk of self-heating and self-ignition under long term exposure to high temperatures. No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid exposure to high temperatures or direct sunlight.
Incompatible materials	Strong acids, alkalies and oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of vapors/fumes generated by heating this product may cause respiratory irritation with throat discomfort, coughing or difficulty breathing. Inhalation of dusts may cause respiratory irritation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Health injuries are not known or expected under normal use. Dust in the eyes will cause irritation. Fumes released during thermal processing may cause eye irritation.
Ingestion	Health injuries are not known or expected under normal use.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity SEBS Maleated	Not classified.	USP Systemic Toxicity Study in Mice – Extract:, No significant and/or relevant adverse effects reported.; for a representative substance.
Skin corrosion/irritation Irritation Corrosion - Skin SEBS Maleated	Not classified.	USP Intracutaneous Study in Rabbits – Extract:, for a representative substance. Result: Negative.
Serious eye damage/eye irritation	No data available.	
Respiratory or skin sensitization		
Respiratory sensitization	No data available.	
Skin sensitization	Not classified.	
Sensitization SEBS Maleated		Tests for irritation and skin sensitization, for a representative substance. Result: Negative. Notes: ISO 10993-10 Guinea Pig Maximization Sensitization Test
Skin sensitization Kraton™ FG Polymers (SEBS Maleated)		Guinea pig maximization test Result: No evidence of dermal sensitization
Germ cell mutagenicity Mutagenicity SEBS Maleated	Not classified.	In Vitro Bacterial Mutagenicity Study in E.Coli and S.Typhimurium from extract., for a representative substance. Result: Negative.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Further information SEBS Maleated	In Vitro Haemolysis Study in Red Blood Cells, Japanese MHLW:;, No significant and/or relevant adverse effects reported.; for a representative substance. ISO 10993-5 Elution Method In Vitro Cytotoxicity Study, No significant and/or relevant adverse effects reported.; for a representative substance. USP Muscle Implantation Study in Rabbits – 7 Day:;, No significant and/or relevant adverse effects reported.; for a representative substance.	

12. Ecological information

Ecotoxicity No data available.

Components	Species	Test Results
SEBS Maleated Aquatic <i>Acute</i> Fish	LC50 Rainbow Trout	> 1000 mg/l, 96 hr
Persistence and degradability	Not inherently biodegradable.	
Bioaccumulative potential	The product is not bioaccumulating.	
Mobility in soil	No data available.	
Other adverse effects	Not available.	
13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Waste from residues / unused products	Dispose of in accordance with local regulations.	
Contaminated packaging	Not applicable.	
14. Transport information		
DOT		
Not regulated as dangerous goods.		
IATA		
Not regulated as dangerous goods.		
IMDG		
Not regulated as dangerous goods.		
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.	
15. Regulatory information		
US federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
Toxic Substances Control Act (TSCA)	All components are either listed on the US EPA TSCA Inventory list and designated as "active" or are exempt from listing.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)		
Not regulated.		
CERCLA Hazardous Substance List (40 CFR 302.4)		
Not listed.		
SARA 304 Emergency release notification		
Not regulated.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
Superfund Amendments and Reauthorization Act of 1986 (SARA)		
SARA 302 Extremely hazardous substance		
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting)		
Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List		
Not regulated.		
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)		
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	

16. Other information, including date of preparation or last revision

Issue date 08-17-2017
Revision date 01-30-2024
Version # 2.2
NFPA ratings Health: 0
Flammability: 1
Instability: 0

NFPA ratings



Disclaimer

KRATON CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information set forth in this document, as of the date of this document, is based on present knowledge, obtained from reliable sources and made to our reasonable ability and in good faith. Such information is made without any warranty or guarantee whatsoever, and shall establish no legal duty or responsibility on the part of the author(s), their employer or its affiliates. The information given is designed only as guidance and its completeness is not guaranteed. The information is not a guarantee of any specific product properties, features, qualities or specifications.

The information relates only to the specific product designated as shipped, and may not be valid for such product used in combination with any other materials or products, or in any process, unless expressly specified in this document. Nothing set forth in this document shall be construed as a recommendation or license to use any product in conflict with, or as claimed by, any existing patents rights. The user alone must finally determine whether a contemplated use of a product will infringe any such patents. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities are in compliance with all Local, Federal and International Legislation and Local Permits.

We, for ourselves and on behalf of our affiliates, expressly disclaim any and all liability for any damages or injuries arising out of any activities relating in any way to the information set forth in this document. Due to the proliferation of sources for information, we are not and cannot be responsible for SDSs obtained from any other source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

*KRATON, the KRATON logo, the "Green Super Drop" logo, 1101, ABIETA, AQUATAC, BiaXam, BI-THIN, CENTURY, CENWAX, CirKular+, ELEXAR, ELLAMERA, E-LEXAR, HiMA, IMSS, IPD, NEXAR, PER-SUST, PriMul, RAD-THICK, REFLECTAID, REvolution, SYLFAT, SYLVABIND, SYLVABLEND, SYLVACLEAR, SYLVACOTE, SYLVADERM, SYLVAFUEL, SYLVAGEL, SYLVAGUM, SYLVALITE, SYLVAMIN, SYLVAPINE, SYLVAPRINT, SYLVARES, SYLVAROAD, SYLVAROS, SYLVASOLV, SYLVATAC, SYLVATAL, SYLVATRAXX, TER-SET, UNICLEAR, UNIDYME, UNIFLEX, UNI-REZ, UNI-TAC, and ZONATAC are either trademarks or registered trademarks of Kraton Corporation, or its subsidiaries or affiliates, in one or more, but not all countries.

©2016-2024 Kraton Corporation

Revision information

Product and Company Identification: Product and Company Identification
Composition / Information on Ingredients: Disclosure Overrides
Regulatory Information: Regulatory Information
Other information, including date of preparation or last revision: Disclaimer
Material Attributes & Uses; Experimental Data: Material Attributes
HazReg Data: Pacific Rim